

Narrowband Ferrite Junction Isolators and Circulators

FEATURES

- ❖ Low Cost, High Quality
- ❖ Compact Size, Light Weight
- ❖ High Performance
- ❖ Wide Operation Temperature Range
- ❖ Common Wireless Communication Frequency Bands in 2 to 110 GHz range

APPLICATIONS

- ❖ Load isolation
- ❖ Receiver input VSWR
- ❖ Transmitter output VSWR
- ❖ Transceiver Diplexers



CJI & CJC Series

SPECIFICATIONS

Waveguide Band	K	WR-34	Ka	Q	U	V	E	W
Frequency Range (GHz)	18.0-26.5	22-33	26.5-40	33-50	40-60	50-75	60-90	75-110
Bandwidth (GHz min)	3.0	2.0	3.0	2.0	1.8	1.5	1.5	1.5
Waveguide Size	WR-42	WR-34	WR-28	WR-22	WR-19	WR-15	WR-12	WR-10
Isolation (dB min)	20.0	20.0	20.0	20.0	15.0	15.0	15.0	15.0
Insertion Loss (dB max)	0.3	0.4	0.4	0.5	0.7	1.0	1.0	1.0
CW Power (W) F/B*	30/1.5	25/1.0	25/1.0	25/0.8	15/0.4	10/0.3	10/0.2	10/0.2
VSWR (max)	1.3:1	1.3:1	1.3:1	1.3:1	1.35:1	1.4:1	1.4:1	1.4:1

ISOLATORS:

Model No.	Frequency Range (GHz)	Band Width (MHz)	Insertion Loss (dB Max)	Isolation (dB Min)	VSWR (Max)	Operating Temp (°C)	Size L x W x H (mm)	Waveguide Type
*CJI04060323S-XX	4.0-6.0	300	0.3	23	1.15	-20 to +60	60 x 110 x 64	WR187
*CJI05070323S-XX	5.0-7.0	300	0.3	23	1.15	-20 to +60	50 x 100 x 62	WR159
*CJI05080325G-XX	5.38-8.17	500	0.3	25	1.20	-40 to +80	45 x 95 x 49	WR137
*CJI05080420G-XX	5.38-8.17	1000	0.4	20	1.25	-40 to +80	45 x 95 x 49	WR137
*CJI05080325S-XX	5.9-8.5	400	0.3	25	1.15	-20 to +60	42 x 80 x 49	WR137
*CJI06090323G-XX	6.57-9.99	500	0.3	23	1.20	-40 to +80	36 x 75.5 x 48	WR112
*CJI06090420G-XX	6.57-9.99	1000	0.4	20	1.25	-40 to +80	36 x 75.5 x 48	WR112
*CJI07100325S-XX	7.1-10.0	600	0.3	25	1.15	-20 to +60	36 x 65 x 48	WR112
*CJI08120423S-XX	8.2-12.0	400	0.4	23	1.20	-20 to +60	12.7 x 48.5 x 42	WR90



Narrowband Ferrite Junction Isolators and Circulators

Model No.	Frequency Range (GHz)	Band Width (MHz)	Insertion Loss (dB Max)	Isolation (dB Min)	VSWR (Max)	Operating Temp (°C)	Size L x W x H (mm)	Waveguide Type
*CJI08120325G-XX	8.2-12.5	300	0.3	25	1.20	-40 to +80	12.7 x 48.5 x 42	WR90
*CJI08120420G-XX	8.2-12.5	500	0.4	20	1.25	-40 to +80	12.7 x 48.5 x 42	WR90
*CJI08120323G-XX	8.2-12.5	1000	0.3	23	1.20	-40 to +80	28 x 56 x 42	WR90
*CJI08120420G-XX	8.2-12.5	2000	0.4	20	1.25	-40 to +80	28 x 56 x 42	WR90
*CJI08090323G	8.6-9.6	-	0.3	23	1.20	-40 to +85	CE01	WR90
*CJI09150320G-XX	9.84-15.0	300	0.3	20	1.20	-40 to +80	12.7 x 43 x 38	WR75
*CJI09150320G1-XX	9.84-15.0	600	0.3	20	1.20	-40 to +80	12.7 x 43 x 38	WR75
*CJI09150323G-XX	9.84-15.0	1000	0.3	23	1.20	-40 to +80	25 x 52 x 38	WR75
*CJI09150420G-XX	9.84-15.0	2000	0.4	20	1.25	-40 to +80	25 x 52 x 38	WR75
*CJI10100228G	10.0-10.3	-	0.25	28	1.15	-40 to +85	CH25	WR90
*CJI10140423S-XX	10.0-14.0	400	0.4	23	1.20	-20 to +60	12.7 x 48 x 38	WR75
*CJI10100320G	10.1-10.7	-	0.3	20	1.20	-40 to +85	CE11	WR75
*CJI10110320G	10.7-11.2	-	0.3	20	1.20	-40 to +85	CE11	WR75
*CJI10120420G	10.7-12.7	-	0.4	20	1.22	-40 to +85	CE02	WR75
*CJI11110320G	11.2-11.7	-	0.3	20	1.20	-40 to +85	CE11	WR75
*CJI11180323G-XX	11.9-18.0	500	0.3	23	1.15	-40 to +80	12.7 x 38.2 x 33.3	WR62
*CJI11180420G-XX	11.9-18.0	1000	0.4	20	1.20	-40 to +80	12.7 x 38.2 x 33.3	WR62
*CJI11180323G1-XX	11.9-18.0	1000	0.3	23	1.20	-40 to +80	21 x 52 x 33.3	WR62
*CJI11180420G1-XX	11.9-18.0	2000	0.4	20	1.25	-40 to +80	21 x 52 x 33.3	WR62
*CJI12120225G	12.0-12.5	-	0.25	25	1.15	-40 to +85	CH26	WR75
*CJI12170423S-XX	12.0-17.0	400	0.4	23	1.20	-20 to +60	9.5 x 38 x 33	WR62
*CJI12130320G	12.7-13.3	-	0.3	20	1.20	-40 to +85	CE11	WR75
*CJI14150420G	14.3-15.45	-	0.4	20	1.20	-40 to +85	CE03	WR62
*CJI14220323G-XX	14.5-22.0	1000	0.3	23	1.20	-40 to +80	15 x 40 x 30.2	WR51
*CJI14220420G-XX	14.5-22.0	2000	0.4	20	1.25	-40 to +80	15 x 40 x 30.2	WR51
*CJI16170423G	16.0-17.0	-	0.4	23	1.20	-40 to +85	CE03	WR62
*CJI17180323G	17.0-18.0	-	0.3	23	1.20	-40 to +85	CE04	WR51
*CJI17260323G-XX	17.6-26.7	1000	0.3	23	1.20	-40 to +80	9.52 x 31.7 x 22.35	WR51
*CJI17260323G1-XX	17.6-26.7	1000	0.3	23	1.20	-40 to +80	12.7 x 32 x 22.4	WR42
*CJI17260323G2-XX	17.6-26.7	1000	0.3	23	1.20	-40 to +80	12.7 x 38.1 x 22.3	WR42
*CJI17260420G-XX	17.6-26.7	2000	0.4	20	1.25	-40 to +80	9.52 x 31.7 x 22.35	WR42
*CJI17260420G1-XX	17.6-26.7	2000	0.4	20	1.22	-40 to +80	12.7 x 32 x 22.4	WR42
*CJI17260420G2-XX	17.6-26.7	2000	0.4	20	1.22	-40 to +80	12.7 x 38 x 22.3	WR42
*CJI17190420G	17.7-19.7	-	0.4	20	1.20	-40 to +85	CE12	WR42
*CJI18260423S-XX	18.0-26.0	1000	0.4	23	1.20	-20 to +60	12.7 x 29 x 22	WR42



Narrowband Ferrite Junction Isolators and Circulators

Model No.	Frequency Range (GHz)	Band Width (MHz)	Insertion Loss (dB Max)	Isolation (dB Min)	VSWR (Max)	Operating Temp (°C)	Size L x W x H (mm)	Waveguide Type
*CJI19210320G	19.6-21.2	-	0.3	20	1.20	-10 to +90	CH32	WR51
*CJI21210328G	21.0-21.5	-	0.3	28	1.15	-40 to +85	CH27	WR42
*CJI21230420G	21.2-23.6	-	0.4	20	1.20	-40 to +85	CE12	WR42
*CJI21330323G1-XX	21.2-33.0	1000	0.3	23	1.20	-40 to +80	9.52 x 31.75 x 22.3	WR34
*CJI21330420G1-XX	21.2-33.0	2000	0.4	20	1.25	-40 to +80	9.52 x 31.75 x 22.3	WR34
*CJI21330323G-XX	21.7-33.0	1000	0.3	23	1.20	-40 to +80	12.7 x 32 x 21.1	WR34
*CJI21330420G-XX	21.7-33.0	2000	0.4	20	1.20	-40 to +80	12.7 x 32 x 21.1	WR34
*CJI24260420G	24.5-26.5	-	0.4	20	1.20	-40 to +85	CE05	WR42
*CJI24260420G1	24.5-26.7	-	0.4	20	1.20	-40 to +85	CE12	WR42
*CJI26400325G-XX	26.3-40.0	1000	0.3	25	1.20	-40 to +80	10 x 28 x 19.1	WR28
*CJI26400322G-XX	26.3-40.0	2000	0.35	22	1.22	-40 to +80	10 x 28 x 19.1	WR28
*CJI26400420G-XX	26.3-40.0	3000	0.4	20	1.22	-40 to +80	12.7 x 32 x 19.56	WR28
*CJI27290420G1	27.0-29.5	-	0.4	20	1.22	-40 to +85	CE13	WR28
*CJI27290420G	27.5-29.5	-	0.4	20	1.20	-40 to +85	CE06	WR34
*CJI31330420G	31.8-33.4	-	0.4	20	1.22	-40 to +85	CE13	WR28
*CJI32500525G-XX	32.9-50.1	1000	0.5	25	1.20	-40 to +80	10 x 26 x 19.1	WR22
*CJI32500623G-XX	32.9-50.1	2000	0.6	23	1.25	-40 to +80	10 x 26 x 19.1	WR22
*CJI33330328G	33-33.5	-	0.3	28	1.15	-40 to +85	CH28	WR28
*CJI35360325G	35.0-36.0	-	0.3	25	1.20	-40 to +85	CE07	WR28
*CJI35360323G	35.5-36.5	-	0.3	23	1.20	-40 to +85	CH33	WR28
*CJI37400420G	37.0-40.0	-	0.4	20	1.22	-40 to +85	CE13	WR28
CJI37400220-XX	37.0-40.0	-	0.2	20	-	-20 to +70	30.5 x 19 x 19	WR28
*CJI39590525G-XX	39.2-59.6	1000	0.5	25	1.20	-40 to +80	10 x 25.5 x 19.1	WR18
*CJI39590623G-XX	39.2-59.6	2000	0.6	23	1.25	-40 to +80	10 x 25.5 x 19.1	WR18
*CJI45460525G	45.0-46.0	-	0.5	25	1.20	-40 to +85	CE08	WR22
*CJI55560525G	55.0-56.0	-	0.5	25	1.20	-40 to +85	CE09	WR18
*CJI87960625G-XX	87.0-96.0	1000	0.6	25	1.25	-40 to +80	10 x 22 x 19.1	WR10
*CJI87960820G-XX	87.0-96.0	2000	0.8	20	1.30	-40 to +80	10 x 22 x 19.1	WR10
*CJI92930625G	92.0-93.0	-	0.6	25	1.25	-40 to +85	CE010	WR10
CJI92941018-XX	92-94	-	1.0	18	1.3	-40 to +85	22 x 19 x 10	Wr10

OTHER FREQUENCY BANDS ARE ALSO AVAILABLE.

*THE SPECIFICATIONS FOR THESE MODELS ARE ONLY FOR THE SPECIFIED FREQUENCY BW.



Narrowband Ferrite Junction Isolators and Circulators

Y-JUNCTION CIRCULATORS:

Model No.	Frequency Range (GHz)	Band Width (MHz)	Insertion Loss (dB Max)	Isolation (dB Min)	VSWR (Max)	Operating Temp. (°C)	Size LXWXH (mm)	Waveguide Type
*CJC04060323S-XX	4.0-6.0	300	0.3	23	1.15	-20 to +60	100X108X64	WR187
*CJC05070323S-XX	5.0-7.0	300	0.3	23	1.15	-20 to +60	90X91X62	WR159
*CJC05080325S-XX	5.9-8.5	400	0.3	25	1.15	-20 to +60	70X70X49	WR137
*CJC06090323G-XX	6.57-9.99	500	0.3	23	1.15	-40 to +80	60X65X47.8	WR112
*CJC06090320G-XX	6.57-9.99	1000	0.3	20	1.25	-40 to +80	60X65X47.8	WR112
*CJC07100325S-XX	7.1-10.0	600	0.3	25	1.15	-20 to +60	60X59X48	WR112
*CJC08120325S-XX	8.2-12.0	1000	0.3	25	1.15	-20 to +60	46X53X42	WR90
*CJC08120323G-XX	8.2-12.5	1000	0.3	23	1.15	-40 to +80	48X53X42	WR90
*CJC08120420G-XX	8.2-12.5	2000	0.4	20	1.25	-40 to +80	48X53X42	WR90
*CJC09150325G-XX	9.84-15.0	1000	0.3	25	1.15	-40 to +80	42X48X38	WR75
*CJC09150420G-XX	9.84-15.0	2000	0.4	20	1.25	-40 to +80	42X48X38	WR75
*CJC10140323S-XX	10.0-14.0	1000	0.3	25	1.15	-20 to +60	44X52X38	WR75
*CJC11180323G-XX	11.9-18.0	1000	0.3	23	1.15	-40 to +80	40X40X33.3	WR62
*CJC11180420G-XX	11.9-18.0	2000	0.4	20	1.25	-40 to +80	40X40X33.3	WR62
*CJC12170325S-XX	12.0-17.0	1000	0.3	25	1.15	-20 to +60	38X38X33	WR62
*CJC14220323G-XX	14.5-22.0	1000	0.3	23	1.15	-40 to +80	32X35X30.2	WR51
*CJC14220420G-XX	14.5-22.0	2000	0.4	20	1.25	-40 to +80	32X35X30.2	WR51
*CJC17260323G-XX	17.6-26.7	1000	0.3	23	1.15	-40 to +80	24X27X22.4	WR42
*CJC17260420G2-XX	17.6-26.7	2000	0.4	20	1.25	-40 to +80	24X27X22.4	WR42
*CJC18260423S-XX	18.0-26.0	1000	0.4	23	1.20	-20 to +60	25X28X22	WR42
*CJC21330323G-XX	21.7-33.0	1000	0.3	23	1.15	-40 to +80	22.3X27X21.2	WR34
*CJC21330420G-XX	21.7-33.0	2000	0.4	20	1.25	-40 to +80	22.3X27X21.2	WR34
*CJC26400323G-XX	26.3-40.0	500	0.3	23	1.20	-40 to +80	21X24X19.1	WR28
*CJC26400323G1-XX	26.3-40.0	1000	0.3	23	1.20	-40 to +80	21X24X19.1	WR28
*CJC26400325G2-XX	26.3-40.0	500	0.3	25	1.15	-40 to +80	10X24.5X19.1	WR28
*CJC26400320G4-XX	26.3-40.0	1000	0.3	20	1.25	-40 to +80	10X24.5X19.1	WR28
*CJC26400325G3-XX	26.3-40.0	500	0.3	25	1.15	-40 to +80	10X24.5X32	WR28
*CJC26400320G5-XX	26.3-40.0	1000	0.3	20	1.25	-40 to +80	10X24.5X32	WR28
*CJC26400423S-XX	26.5-40.0	2000	0.4	23	1.20	-20 to +60	20X25X20	WR28
*CJC27290420G	27.0-29.5	-	0.4	20	1.25	-40 to +85	CF11	WR28
*CJC31330420G	31.8-33.4	-	0.4	20	1.25	-40 to +85	CF11	WR28
*CJC32500523G-XX	32.9-50.1	1000	0.5	23	1.20	-40 to +85	19.1X20X19.1	WR22
*CJC32500620G-XX	32.9-50.1	2000	0.6	20	1.25	-40 to +80	19.1X20X19.1	WR22
CJC33340650G	33.75-34.75	Full	0.6	50	1.20	-60 to +80	30X62X20	WR28



Narrowband Ferrite Junction Isolators and Circulators

Model No.	Frequency Range (GHz)	Band Width (MHz)	Insertion Loss (dB Max)	Isolation (dB Min)	VSWR (Max)	Operating Temp. (°C)	Size LXWXH (mm)	Waveguide Type
*CJC37400418G	37.0-40.0	-	0.4	18	1.30	-40 to +85	CF11	WR28
*CJC39590523G-XX	39.2-59.6	1000	0.5	23	1.20	-40 to +80	10X24.5X19.1	WR18
*CJC39590620G1-XX	39.2-59.6	2000	0.6	20	1.25	-40 to +80	10X24.5X19.1	WR18
*CJC39590523G2-XX	39.2-59.6	1000	0.5	23	1.20	-40 to +80	19X19.1X19.1	WR18
*CJC39590620G2-XX	39.2-59.6	2000	0.6	20	1.25	-40 to +80	19X19.1X19.1	WR18
*CJC55560523G	55.0-56.0	-	0.5	23	1.20	-40 to +85	CF09	WR18
*CJC87960623G-XX	87.0-96.0	1000	0.6	23	1.20	-40 to +80	10X25X19.1	WR10
*CJC87960818G-XX	87.0-96.0	2000	0.8	18	1.30	-40 to +80	10X25X19.1	WR10
*CJC92930623G	92.0-93.0	-	0.6	23	1.20	-40 to +85	CF10	WR10

OTHER FREQUENCY BANDS ARE ALSO AVAILABLE.

*THE SPECIFICATIONS FOR THESE MODELS ARE ONLY FOR THE SPECIFIED FREQUENCY BW.

UNI JUNCTION CIRCULATORS:

Model No.	Frequency Range (GHz)	Band Width (MHz)	Insertion Loss (dB Max)	Isolation (dB Min)	VSWR (Max)	Operating Temp. Range (°C)	Size LXWXH (mm)	Waveguide Type
*CJC05060320G	5.8-6.4	-	0.3	20	1.20	-40 to +85	CH34	WR137
*CJC07080423G	7.7-8.4	-	0.4	23	1.15	-40 to +85	CF01	WR112
*CJC07080423G1	7.8-8.4	-	0.4	23	1.25	-40 to +85	CH35	WR112
*CJC08090323G	8.6-9.6	-	0.3	23	1.15	-40 to +85	CF02	WR90
*CJC10100228G	10.0-10.3	-	0.25	28	1.15	-40 to +85	CH29	WR90
*CJC10120420G	10.7-12.7	-	0.4	20	1.25	-40 to +85	CF03	WR75
*CJC12120228G	12.0-12.3	-	0.25	28	1.15	-40 to +85	CH30	WR75
*CJC16170323G	16.0-17.0	-	0.3	23	1.15	-40 to +85	CF04	WR62
*CJC17180323G	17.0-18.0	-	0.3	23	1.15	-40 to +85	CF05	WR51
*CJC24260420G	24.5-26.5	-	0.4	20	1.25	-40 to +85	CF06	WR42
*CJC33350328G	33.0-33.5	-	0.3	28	1.15	-40 to +85	CH31	WR28
*CJC35360323G	35.0-36.0	-	0.3	23	1.20	-40 to +85	CF07	WR28
*CJC45460523G	45.0-46.0	-	0.5	23	1.20	-40 to +85	CF08	WR22

OTHER FREQUENCY BANDS ARE ALSO AVAILABLE.

*THE SPECIFICATIONS FOR THESE MODELS ARE ONLY FOR THE SPECIFIED FREQUENCY BW.



Narrowband Ferrite Junction Isolators and Circulators

HOW TO ORDER

Specify model numbers when ordering. For units with specifications not listed, specify the model number using the following notation :

CJI+LF+HF+IL+IS-XX
or ***CJC+LF+HF+IL+IS-XX***

where ***CJI*** = Narrowband Junction Isolator
CJC = Narrowband Junction Circulator
LF = Low Frequency Range
HF = High Frequency Range
IL = Insertion Loss
IS = Isolation
XX = To be specified by factory at time of order

Example: To order a 1.8-2.0 GHz isolator with 0.3 dB maximum insertion loss and 20 dB minimum isolation and, specify CJI01020320-XX.