

CCK06NM

6GHz 50Ω N Type Mechanical Calibration Kit

Overview

The 6GHz CALKIT is used to calibrate network analyzers for measurements of components with N type connectors. The Frequency Range is DC~6GHz.

Model #	Description	Qty
CNM06OC	Open (male)	1
CNM06SC	Short (male)	1
CCLDC06MC	Load (male)	1
CNM-NM06C	Adapter (male to male)	1
CNF-NF06C	Adapter (female to female)	1
CNM-NF06C	Adapter (male to female)	1
CTWN	Torque Wrench	1
	Box	1

Interface Dimensions



	mm		inchs	
	Min.	Max.	Min.	Max.
a	6.99	7.01	0.2751	0.2761
b	7.98	8.04	0.3140	0.3165
d	3.04		0.120	
e	5.26	5.30	0.2070	0.2086
p	1.638	1.664	0.0645	0.0655
q	—	0.076	—	0.003

	mm		inchs	
	Min.	Max.	Min.	Max.
a	6.99	7.01	0.2751	0.2761
b	8.05	8.1	0.317	0.319
d	3.04		0.120	
e	5.22	5.26	0.2055	0.2070
f	9.07	9.17	0.357	0.361
s	7	—	0.2755	—
ae	1.80	1.91	0.071	0.075

Electrical Specifications

- ✧ Impedance : 50Ω
- ✧ Average Power : ≤1W
- ✧ Electrical Specifications :

Description	Frequency	Specifications
loads	DC~6GHz	Return Loss -38dB VSWR 1.025
opens	DC~6GHz	Deviation from Nominal Phase±0.8°
shorts	DC~6GHz	Deviation from Nominal Phase±0.8°
adapters	DC~9GHz (operating up to 18GHz), Return loss: -32dB, VSWR: -1.05, Insertion loss: 0.1dB	

Materials

Center conductor : beryllium bronze
 Body : stainless steel
 Connector nut : stainless steel

Standard

IEC 60169-16 Grade 0

Mechanical Characteristic

Connect/disconnect life : >500 times
 Maximum insertion force : 8.9N
 Coupling torque : 1.35 Nm
 Open-end wrench size : 19mm

Environmental Requirements

Parameter	Limits
Operating Temperature	+20°C~ +26°C (suggested)
Storage Temperature	-40°C~ +75°C

